

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****X ST73770#SR-00821-00002 Safety Yellow**Version Number 1.0
Revision Date 07/31/2012Page 1 of 8
Print Date 8/28/2012**1. PRODUCT AND COMPANY IDENTIFICATION****POLYONE CORPORATION**
33587 Walker Road, Avon Lake, OH 44012Telephone : 1 (440) 930-1000 or 1 (866) POLYONE
Emergency telephone : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).**Product name : X ST73770#SR-00821-00002 Safety Yellow
Product code : EM10026175
Chemical Name : Mixture
CAS-No. : Mixture
Product Use : Industrial Applications**2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS**

Components	CAS-No.	Weight percent
Styrene	100-42-5	0.1 - 1
Titanium dioxide	13463-67-7	1 - 5

3. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure.

POTENTIAL HEALTH EFFECTS**Routes of Exposure:** : Inhalation, Ingestion, Skin contact**Acute exposure**Inhalation : Particulates, like other inert materials can be mechanically irritating.
Ingestion : May be harmful if swallowed.
Eyes : Particulates, like other inert materials can be mechanically irritating.
Skin : Experience shows no unusual dermatitis hazard from routine handling.**Chronic exposure** : Refer to Section 11 for Toxicological Information.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

X ST73770#SR-00821-00002 Safety Yellow

Version Number 1.0
Revision Date 07/31/2012

Page 2 of 8
Print Date 8/28/2012

Medical Conditions : None known.
Aggravated by Exposure:

4. FIRST AID MEASURES

Inhalation : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.

Ingestion : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.

Eyes : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.

Skin : Wash off with soap and plenty of water. If skin irritation persists seek medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : not applicable

Flammable Limits
Upper explosion limit : not applicable
Lower explosion limit : not applicable

Autoignition temperature : not applicable

Suitable extinguishing media : Carbon dioxide blanket, Water spray, Dry powder, Foam.

Special Fire Fighting Procedures : Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.

Unusual Fire/Explosion Hazards : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), other hazardous materials, and smoke are all possible.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.

Environmental precautions : Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.

Methods for cleaning up : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.

7. HANDLING AND STORAGE

Handling : Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

X ST73770#SR-00821-00002 Safety Yellow

Version Number 1.0

Revision Date 07/31/2012

Page 3 of 8

Print Date 8/28/2012

Storage : Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection : No personal respiratory protective equipment normally required.

Eye/Face Protection : Safety glasses with side-shields

Hand protection : Protective gloves

Skin and body protection : Long sleeved clothing

Additional Protective Measures : Safety shoes

General Hygiene Considerations : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.

Exposure limit(s)

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

X ST73770#SR-00821-00002 Safety Yellow

Version Number 1.0

Page 4 of 8

Revision Date 07/31/2012

Print Date 8/28/2012

Components	Value	Exposure time	Exposure type	List:	
Styrene	20 ppm	Time Weighted Average (TWA):		ACGIH	
	40 ppm	Short Term Exposure Limit (STEL):		ACGIH	
	50 ppm 215 mg/m3	Recommended exposure limit (REL):		NIOSH	
	100 ppm 425 mg/m3	Short Term Exposure Limit (STEL):		NIOSH	
	100 ppm	Time Weighted Average (TWA):		OSHA Z2	
	200 ppm	Ceiling Limit Value:		OSHA Z2	
	600 ppm	Maximum concentration:		OSHA Z2	
	50 ppm 215 mg/m3	Time Weighted Average (TWA):		OSHA Z1A	
	100 ppm 425 mg/m3	Short Term Exposure Limit (STEL):		OSHA Z1A	
	50 ppm 215 mg/m3	Time Weighted Average (TWA):		MX OEL	
	100 ppm 425 mg/m3	Short Term Exposure Limit (STEL):		MX OEL	
	Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
		15 mg/m3	PEL:	Total dust.	OSHA Z1
10 mg/m3		Time Weighted Average (TWA):	Total dust.	OSHA Z1A	
10 mg/m3		Time Weighted Average (TWA):	as Ti	MX OEL	
20 mg/m3		Short Term Exposure Limit (STEL):	as Ti	MX OEL	

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: solid	Evaporation rate	: Not applicable
Appearance	: pellets, Slabs	Specific Gravity	: Not determined
Colour	: YELLOW	Bulk density	: Not established
Odour	: very faint	Vapour pressure	: not applicable
Melting point/range	: Not determined	Vapour density	: not applicable
Boiling Point:	: not applicable	pH	: not applicable
Water solubility	: insoluble		

10. STABILITY AND REACTIVITY

Stability	: Stable
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: To avoid thermal decomposition, do not overheat.

POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

X ST73770#SR-00821-00002 Safety Yellow

Version Number 1.0
Revision Date 07/31/2012

Page 5 of 8
Print Date 8/28/2012

Incompatible Materials : Strong acids, oxidizing and reducing agents
Hazardous decomposition products : Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), other hazardous materials, and smoke are all possible.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
100-42-5	Styrene	Irritant	Eyes, Respiratory system.
		Systemic effects	Eyes, Skin, Respiratory system, Liver, central nervous system (CNS).
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
100-42-5	Styrene	LC50 Oral LD50	12 gm/m ³ 2,650 mg/kg	rat rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
100-42-5	Styrene	no	2B	no
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

- 1 - The component is carcinogenic to humans.
- 2A - The component is probably carcinogenic to humans.
- 2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 - The component is known to be a human carcinogen.
- 2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Styrene 100-42-5 Irritating to eyes, skin, and respiratory tract with many CNS effects such as narcosis, cramps and respiratory tract paralysis.

12. ECOLOGICAL INFORMATION



POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

X ST73770#SR-00821-00002 Safety Yellow

Version Number 1.0
Revision Date 07/31/2012

Page 6 of 8
Print Date 8/28/2012

Persistence and degradability : Not readily biodegradable.
Environmental Toxicity : Chemicals are not readily available as they are bound within the polymer matrix.
Bioaccumulation Potential : Chemicals are not readily available as they are bound within the polymer matrix.
Additional advice : not applicable

13. DISPOSAL CONSIDERATIONS

Product : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

U.S. DOT Classification : Not regulated for transportation.
ICAO/IATA : Refer to specific regulation.
IMO/IMDG (maritime) : Refer to specific regulation.

15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.
TSCA Status : All components of this product are listed on or exempt from the TSCA Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

California Proposition : Not applicable
65

POLYONE CORPORATION**MATERIAL SAFETY DATA SHEET****X ST73770#SR-00821-00002 Safety Yellow**Version Number 1.0
Revision Date 07/31/2012Page 7 of 8
Print Date 8/28/2012

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Chemical Name	CAS-No.	Weight percent
STYRENE	100-42-5	0.10 - 1.00

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight percent	NPRI ID#
Styrene	100-42-5	0.10 - 1.00	

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
100-42-5

DSL : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

- Australia AICS : Not determined
- China IECS : Not determined
- Europe EINECS : Not determined
- Japan ENCS : Not determined
- Korea KECI : Not determined
- Philippines PICCS : Not determined

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing,



POLYONE CORPORATION

MATERIAL SAFETY DATA SHEET

X ST73770#SR-00821-00002 Safety Yellow

Version Number 1.0

Revision Date 07/31/2012

Page 8 of 8

Print Date 8/28/2012

storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.